

## SAFETY DATA SHEET

according to 1907/2006/EC, article 31

CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80



Revision date: 2016-11-23

Version: 1

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### 1.1 Product identifier

Product name: CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80

Substance: ALUMINIUM PASTE IN DI-(2-ETHYLHEXYL)ADIPATE

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Identified uses: Pigments

#### 1.3 Details of the supplier of the safety data sheet.

Manufacturer: CARLFORS BRUK AB  
BOX 44  
SE-561 21 HUSKVARNA SWEDEN  
Tel: +46 36389500  
Fax: +46 36141754  
E-mail: cb@carlfors.se

#### 1.4 Emergency telephone number.

Emergency number: +46 8337043

### SECTION 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture:

Classification according to: CLP/GHS EC No 1272/2008.

Not classified.

Note T regulation (EC) No 1272/2008: This product may be marketed in a form which does not have the physical hazards as indicated in the entry in part 3. Tests were done according to Transport of dangerous goods, Manual of tests and criteria.

Additional Information: See section 16.

#### 2.2 Label elements:

Label elements according to Regulation (EC) No 1272/2008 (CLP).

Hazard pictograms:

Signal word:

Hazard Statements:

## SAFETY DATA SHEET

according to 1907/2006/EC, article 31

CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80



Revision date: 2016-11-23

Version: 1

### Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370 + P378 In case of fire, use sand and/or rock wool, foam or carbon dioxide. Never use water

P402 + P404 Store in a dry place. Store in a closed container.

### 2.3 Other hazards:

No additional information available.

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substances

### 3.2 Mixtures

Chemical name	Cas-no:	Einecs no:	REACH registration no:	Contents %
Aluminium powder	7429-90-5	231-072-3	01-2119529243-45-0051	78-82
GHS/CLP-classification:*	Flam. Sol. 1, H228			

Chemical name	Cas-no:	Einecs no:	REACH registration no:	Contents %
Di-(2-ethylhexyl)adipate	103-23-1	203-090-1	01-2119439699-19-xxxx	18-22
GHS/CLP-classification:*	-			

\* See section 16.

## SECTION 4. FIRST-AID MEASURES

### 4.1 Description of first aid measures:

**General information:** No additional information available.

**Inhalation:** Fresh air and rest.

**Skin contact:** Take of contaminated clothes, wash skin with water and soap.

**Eye contact:** Remove any contact lenses. Rinse immediately with plenty of water, also under the eyelids. Call doctor if irritation persists.

**Ingestion:** Don't induce vomiting. Call doctor. Rinse mouth and drink water.

**4.2 Most important symptoms and effects, both acute and delayed:** No further relevant information.

**4.3 Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

## SECTION 5. FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media:

## SAFETY DATA SHEET

according to 1907/2006/EC, article 31

CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80



Revision date: 2016-11-23

Version: 1

**Suitable extinguishing agents:** Extinguish fire with sand and mineral wool. Can also be extinguished with foam or carbon dioxide during the first minutes when the solvent in the aluminium paste is burning. After a short time, when the solvent has burned, it is a metal fire, and then only use sand, mineral wool or special powder for metal fires.

**Unsuitable extinguishing agents:** Do not use water.

**5.2 Special hazards arising from the substance or mixture:** No further relevant information available.

**5.3 Advice for firefighters:** No special measures required.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Eliminate fire risk by keeping ignition sources out of the area.

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or water resources. Inform authorities in case product reaches water or sewage system.

### 6.3 Methods and material for containment and cleaning up:

Collect mechanically. Absorb with liquid binding material (sand, diatomite, universal binders, sawdust) and put in a dry receptacle. Do not flush with water or aqueous cleaning agents. Dispose of waste material in accordance with local, state or federal regulations.

### 6.4 Reference to other sections:

See section 8 for protective equipment. See section 13 for waste treatment methods.

## SECTION 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

Mechanical ventilation and local exhaust can be needed. Keep drums closed as far as possible. Avoid direct contact with aluminium paste. No smoking, fire, sparks or welding. Prevent sparks arising from static electricity.

Wash hands during breaks and at the end of the work. Keep away from foodstuffs, beverages and feed. Do not eat, drink, smoke or sniff while working. Water for eye flushing to be available.

### 7.2 Conditions for safe storage, including any incompatibilities:

Store in a cool, dry place in tightly closed containers. Keep away from sources of ignition-No smoking.

### 7.3 Specific end use(s):

See section 1, identified uses.

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters:

Aluminium powder: DNEL long-term, worker, for aluminium metal powder/dust is 3,72 mg aluminium/m<sup>3</sup>. PNEC-values from 46-17800 µg/l depending on water chemistry.

DNEL long-term, worker, for Di-(2-ethylhexyl)adipate: Dermal 25,5 mg/kg/day. Inhalation 17,8 mg/m<sup>3</sup>. PNEC fresh water 0,0032 mg/l.

**Occupational exposure limits ( limit value - eight hours):**

**SAFETY DATA SHEET**

according to 1907/2006/EC, article 31

**CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80**

Revision date: 2016-11-23

Version: 1

	Aluminium powder
Austria	10 mg/m3
Canada - Québec	10 mg/m3
Denmark	5 mg/m3 (inhalable aerosol) 2 mg/m3 (respirable)
France	10 mg/m3 (inhalable aerosol) 5 mg/m3 (respirable aerosol)
Germany	4 mg/m3 (inhalable aerosol) 1,5 mg/m3 (respirable aerosol)
Hungary	6 mg/m3 (respirable aerosol)
Spain	5 mg/m3 (respirable aerosol) 10 mg/m3 (inhalable aerosol)
United Kingdom	4 mg/m3 (respirable aerosol) 10 mg/m3 (inhalable aerosol)
USA	15 mg/m3 (total dust) 5 mg/m3 (respirable dust)

**8.2 Exposure controls:**

**General protective and hygienic measures:** Wash hands during breaks and at the end of the work. Keep away from foodstuffs, beverages and feed. Do not eat, drink, smoke or sniff while working.

**Personal protective equipment:**

**Breathing equipment:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements. Filter against organic vapors.

**Protection of hands:** Protective gloves of for example nitrile rubber . Change protective gloves regularly.

**Eye protection:** Protective goggles if there is a risk of splashing.

**Skin protection:** Protective clothing.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

\* Refer to di-(2-ethylhexyl)adipate

**9.1 Information on basic physical and chemical properties:**

<b>Appearance</b>	Paste , gray
<b>Odour</b>	* Odourless
<b>Odour threshold</b>	* No information
<b>pH</b>	NA
<b>Melting point/freezing point (°C)</b>	* -68
<b>Initial boiling point/boiling range (°C)</b>	* 210-218
<b>Flash point (°C)</b>	* 196
<b>Evaporation rate</b>	* No information
<b>Flammability (solid, gas)</b>	Not classified as flammable solid.

## SAFETY DATA SHEET

according to 1907/2006/EC, article 31

CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80



Revision date: 2016-11-23

Version: 1

Upper/lower flammability/explosive limits	* No information
Vapour pressure (kPa)	* No information
Vapour density (air=1)	* No information
Density (g/cm <sup>3</sup> )	0,8-1,2 (Density = volume weight)
Solubility in water (weight-%)	* Insoluble
Partition coefficient, log Pow	* 8,94
Auto-ignition temperature (°C)	* 377
Decomposition temperature (°C)	* No information
Viscosity	NA
Explosive properties	No
Oxidising properties	No
9.2 Other information:	No additional information.

### SECTION 10. STABILITY AND REACTIVITY

#### 10.1 Reactivity:

Not classified as flammable solid.

#### 10.2 Chemical Stability:

The product is stable if used and stored according to specifications.

#### 10.3 Possibility of hazardous reactions:

Hydrogen development with water, alkali and acid.

#### 10.4 Conditions to avoid:

Keep away from sources of ignition and heat.

#### 10.5 Incompatible material:

Reacts with alkalis, acids, water and oxidizing agents.

#### 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

Aluminium powder: Oral LD50 (rat) > 2000 mg/kg bw. Inhalation LC50 (rat) > 888 mg/m<sup>3</sup>. Inhalation NOAEC (rat) = 10 mg/m<sup>3</sup>.

Di-(2-ethylhexyl)adipate: Oral LD50 (rat) 45000 mg/kg (OECD 401). Inhalation LC50 (rat) 5,7 mg/l (OECD 403).

Inhalation: High concentrations can be irritating to the respiratory system.

Skin contact: Can cause skin irritation.

Eyes: Causes smart.

**SAFETY DATA SHEET**

according to 1907/2006/EC, article 31

**CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80**

Revision date: 2016-11-23

Version: 1

Ingestion: Can cause indisposition and vomiting.

Aluminum powder and di-(2-ethylhexyl)adipate is not carcinogenic, mutagenic or toxic to reproduction.

**SECTION 12. ECOLOGICAL INFORMATION****12.1 Toxicity:**

Aluminium powder and di-(2-ethylhexyl)adipate is not classified as dangerous for the environment.

Di-(2-ethylhexyl)adipate: LC50 (Oncorhynchus mykiss) 96 hours: 50-150 mg/l. EC50 (daphnia magna) 48 hours: &gt; 500 mg/l.

**12.2 Persistence and degradability:**

Di-(2-ethylhexyl)adipate is readily biodegradable, &gt; 60 % 28 d (OECD 301 C)

**12.3 Bioaccumulative potential:**

No information.

**12.4 Mobility in soil:**

Aluminium paste is a solid material and is not expected to penetrate into the soil.

**12.5 Results of PBT and vPvB assessments:**

This product is not, or does not contain, a substance that is a PBT or a vPvB.

**12.6 Other adverse affects:**

No additional information available.

**SECTION 13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods:**

Dispose of waste material in accordance with local, state or federal regulations. Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue: 12 01 04 – Non-ferrous metal dust and particles.

Empty contaminated packaging thoroughly. They can be recycled after thorough and proper cleaning.

**SECTION 14. TRANSPORT INFORMATION**

	ADR/RID	IATA	IMDG
14.1 UN No			
14.3 Transport hazard class(es)			
14.4 Packing group			
EmS No			
Tunnel category			

Not classified as dangerous goods.

**14.2 UN proper shipping name:****14.5 Environmental hazards:** No

## SAFETY DATA SHEET

according to 1907/2006/EC, article 31

CB 105 DOA 80, CB 180S DOA 80, CB 200S DOA 80, CB 400 DOA 80



Revision date: 2016-11-23

Version: 1

### 14.6 Special precautions for user:

Handling and storage according to section 7.

### 14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code:

NA

## SECTION 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Reference: EC no. 1907/2006, EC no. 1272/2008, EC no. 453/2010, (EU) 2015/830, IFA-databases on hazardous substances (GESTIS), CSR for aluminium and safety data sheet for di-(2-ethylhexyl)adipate.

### 15.2 Chemical safety assessment: No

## SECTION 16. OTHER INFORMATION

H228 Flammable solid.

Flam. Sol. 1 = Flammable solid, category 1

List of abbreviations

ADR Accord Européen relatif au transport international des marchandises dangereuses par Route.

CAS No. Chemical abstracts service number.

CLP Regulation on Classification, Labelling and packaging of Substances and Mixtures.

CSR Chemical safety report

DNEL Derived NO-Effect Level.

EINECS European Inventory of Existing Commercial Substances.

EWC European Waste Catalogue.

IATA International Air Transport Association

ICAO International Civil Aviation Organization

IMDG International Maritime Dangerous Goods

IMO International Maritime Organization

LC Lethal Concentration

LD Lethal Dose

Marpol International Convention for the Prevention of Pollution from ships.

NOAL No observable adverse effect level.

NOEL/NOEC No observed – effect level/concentration.

PBT Persistent, biaccumulative, toxic.

PNEC Predicted No-Effect Concentration.

REACH Registration, Evaluation, Authorisation, and restriction of Chemicals.

RID Règlement concernant le transport international ferroviaire de marchandises dangereuses.

TWA Time-weighted average.

vPvB Very persistent, very biaccumulative