SAFETY DATA SHEET

according to 1907/2006/EC, article 31

CB 105 65, CB 180 65, CB 180S 65, CBright 180S 65, CB 200S 65, CB 400 WS 65

Revision date: 2023-12-04
Version: 18, revision 17
Replace: 2023-09-18

SECTION 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Product name:	CB 105 65, CB 180 65, CB 180S 65, CBright 180S 65, CB 200S 65, CB 400 WS 65
Substance:	ALUMINIUM PASTE IN WHITE SPIRIT, LOW AROMATIC/HIGH AROMATIC
UFI:	FE00-V0DD-H00E-WWMK

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Identified uses: Pigments

1.3 Details of the supplier of the safety data sheet.

Manufacturer: CARLFORS BRUK AB
BOX 44
SE-561 21 HUSKVARNA SWEDEN
Tel: +46 36389500
E-mail: cb@carlfors.se

1.4 Emergency telephone number.

Emergency number: +46 8337043

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

Classification according to: CLP/GHS EC No 1272/2008.

Flam. Sol. 1. H228
Stot SE 3. H336
Aquatic Chronic 3. H412
EUH066
Note T regulation (EC) No 1272/2008: This product may be marketed in a form which does not have the physical hazards as indicated in the entry in part 3. Tests were done according to Transport of dangerous goods, Manual of tests and criteria.

Additional Information: See section 16.

2.2 Label elements:

Label elements according to Regulation (EC) No 1272/2008 (CLP).

Hazard pictograms: GHS02, GHS07

Signal word: Danger

Hazard Statements:

H228 Flammable solid.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P370 + P378 In case of fire: Use sand, mineral wool or special powder for metal fire, never use water, halones, foam or carbon dioxide.
P402 + P404 Store in a dry place. Store in a closed container.

2.3 Other hazards:

When heated, material can release vapors which may form flammable mixtures with air. Vapors are heavier than air and may spread along floors. The product is classified as harmful to aquatic life with long lasting effects. This substance/mixture contains no components considered to be either persistent, biaccumulative and toxic (PBT), or very persistent and very biaccumulative (vPvB) at levels of 0,1 % or higher.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

3.2 Mixtures

Chemical name	Cas-no:	Einecs no:	REACH registration no:	Contents %
Aluminium powder (stabilized)	7429-90-5	231-072-3	01-2119529243-45-0051	63-67
GHS/CLP-classification:*	Flam. Sol. 1, H228. refer to note T in EC 1272/2008. Test method in Transport of dangerous goods, Manual of tests and criteria section 33.4, has been used.			

Chemical name	Cas-no:	Einecs no:	REACH registration no:	Contents %
Hydrocarbons, C9-C11, n-alkanes, cyclics, < 2 % aromatics (white spirit)	64742-48-9	919-857-5	01-2119463258-33-xxxx	20-30
GHS/CLP-classification:*	Asp. Tox. 1. H304, Flam. Liq. 3. H226, STOT SE 3. H336, EUH066			

Chemical name	Cas-no:	Einecs no:	REACH registration no:	Contents %
HA = Hydrocarbons, C9, aromatics, < 0,1 % cumene	64742-95-6	918-668-5	01-2119455851-35-xxxx	5-15
GHS/CLP-classification:*	Aquatic Chronic 2. H411, Asp. Tox. 1. H304, Flam. Liq. 3. H226, STOT SE 3. H335, H336, EUH066			

* See section 16.

SECTION 4. FIRST-AID MEASURES

4.1 Description of first aid measures:

General information: No additional information available.

Inhalation: Fresh air and rest, possibly breathing help.

Skin contact: Take of contaminated clothes, wash skin with water and soap.

Eye contact: Remove any contact lenses. Rinse immediately with plenty of water, also under the eyelids. Continue irrigation for several minutes. Call doctor if irritation persists.

Ingestion: Don't induce vomiting. Call doctor. Rinse mouth with water and drink water.

4.2 Most important symptoms and effects, both acute and delayed: See section 11.

4.3 Indication of any immediate medical attention and special treatment needed: No further relevant information available.

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing agents: Extinguish fire with sand and mineral wool. Can also be extinguished with foam or carbon dioxide during the first minutes when the solvent in the aluminium paste is burning. After a short time, when the solvent has burned, it is a metal fire, and then only use sand, mineral wool or special powder for metal fires.

Unsuitable extinguishing agents: Do not use water.

5.2 Special hazards arising from the substance or mixture: When heated, material can release vapors which may form flammable mixtures with air. Vapors are heavier than air and may spread along floors.

5.3 Advice for firefighters: No special measures required.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:
Wear protective equipment. Eliminate fire and explosion risk by keeping ignition sources out of the area.

6.2 Environmental precautions:
Do not allow product to reach sewage system or water resources. Inform authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Collect mechanically. Pay attention to the fire, explosion and health hazards caused by the product. Absorb with liquid binding material (sand, diatomite, universal binders, sawdust) and put in a dry receptacle. Do not flush with water or aqueaous cleaning agents. Dispose of waste material in accordance with local, state or federal regulations.

6.4 Reference to other sections:

See section 7 for safe handling. See section 8 for protective equipment. See section 13 for waste treatment methods.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling:

Good ventilation. Mechanical ventilation and local exhaust can be needed. Keep drums closed as far as possible. Avoid direct contact with aluminium paste. No smoking, fire, sparks or welding. Prevent sparks arising from static electricity.

Wash hands during breaks and at the end of the work. Keep away from foodstuffs, beverages and feed. Do not eat, drink, smoke or sniff while working. Water for eye flushing to be available.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a cool, well-ventilated, dry place in tightly closed containers. Protect from direct sunlight. Keep away from sources of ignition-No smoking.

7.3 Specific end use(s):

See section 1, identified uses.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

DNEL long-term, worker, for aluminium metal powder/dust is 3,72 mg aluminium/m3.
PNEC-values from 46-17800 µg/l depending on water chemistry.

Worker DNEL Chronic Exposure, Systemic Effects Hydrocarbons, C9, aromatics < 0,1 % cumene: Dermal : 25 mg/kg bw/day. Inhalation: 150 mg/m3.

Worker DNEL long-term systemic effects Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics. Inhalation: 871 mg/m3. Dermal 208 mg/kg bw/day.

Occupational exposure limits (limit value - eight hours):

	Aluminium powder (stabilized)
Austria	10 mg/m3
Canada - Québec	10 mg/m3
Denmark	5 mg/m3 (inhalable aerosol)
	2 mg/m3 (respirable)
France	10 mg/m3 (inhalable aerosol)
	5 mg/m3 (respirable aerosol)
Germany	4 mg/m3 (inhalable aerosol)
	1,5 mg/m3 (respirable aerosol)
Hungary	6 mg/m3 (respirable aerosol)
Spain	5 mg/m3 (respirable aerosol)
	10 mg/m3 (inhalable aerosol)
United Kingdom	4 mg/m3 (respirable aerosol)
	10 mg/m3 (inhalable aerosol)
USA	15 mg/m3 (total dust)
	5 mg/m3 (repirable dust)

8.2 Exposure controls:

General protective and hygienic measures: Wash hands during breaks and at the end of the work. Keep away from foodstuffs, beverages and feed. Do not eat, drink, smoke or sniff while working.

Personal protective equipment:

Breathing equipment: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator, type A filter material, European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations. For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode.

Protection of hands: Protective gloves of nitrile rubber. Change protective gloves regularly.

Eye protection: Face shield or protective goggles if there is a risk of splashing.

Skin protection: Protective clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

* Refer to white spirit < 2 % aromatics (WS) and high aromatic (HA)

9.1 Information on basic physical and chemical properties:

Physical state	Paste
Colour	Grey
Odour	* Pungent petroleum
Melting point/freezing point (°C)	* WS pour point -20 HA -50
Initial boiling point/boiling range (°C)	* WS 130-213 HA 155-181
Flammability (solid, gas)	Flammable solid

Lower and upper explosion limit	* WS 0,6-7 vol. % HA 0,8-7 vol. %
Flash point (°C)	* WS > 36 HA 41 (ASTM D 56)
Auto-ignition temperature (°C)	* WS > 200 HA > 450
pH	NA
Solubility in water (weight-%)	* Slightly soluble
Partition coefficient, log Pow (log value)	* No information
Density (g/cm³)	0,8-1,2 (Density = volume weight)
Particle characteristics	Aluminium paste containing aluminium powder with average diameter between 14-30 micrometers. Measuring instrument Malvern. See technical data sheet for more information.
9.2 Other information:	The product is classified as flammable solid. See section 14 for more information.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity:

Flammable solid.

10.2 Chemical Stability:

The product is stable if used and stored according to specifications.

10.3 Possibility of hazardous reactions:

Hydrogen development with water, alkali and acid.

10.4 Conditions to avoid:

Keep away from sources of ignition and heat.

10.5 Incompatible material:

Reacts with alkalis, acids, water and oxidizing agents.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

High aromatic (HA) = Hydrocarbons, C9, aromatics < 0,1 % cumene: Toxicity when swallowed LD50 (rat) > 2000- < 5000 mg/kg (OECD 401). In contact with skin LD50 (rabbit) > 2000 mg/kg (OECD 402).

Aluminium powder: Oral LD50 (rat) > 2000 mg/kg bw. Inhalation LC50 (rat) > 888 mg/m3. Inhalation NOAEC (rat) = 10 mg/m3.

White spirit < 2 % aromatics = Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics: Very low toxicity when swallowed LD50 > 5000 mg/kg (rat). In contact with skin LD50 > 5000 mg/kg (rabbit). Inhaled LC50 > 5 mg/l (rat 4h).

Inhalation: Vapor concentrations above recommended exposure levels may be irritating to the eyes and the respiratory tract, may cause headache and dizziness.

Skin: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eyes: Causes smart.

Ingestion: Can cause indisposition, vomiting and diarrhea.
The symptoms above refer to high aromatic and white spirit < 2 % aromatics.

Serious eye damage/irritation: Based on available data the classification criteria are not met.
CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction): Based on available data the classification criteria are not met.
Aspiration hazard: Based on available data the classification criteria are not met.
STOT – Repeated exposure: Based on available data the classification criteria are not met.

11.2 Information on other hazards:

No further information.

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity:

Aluminium powder and white spirit (< 2 % aromatics) are not classified as dangerous for the environment.

High aromatic (Hydrocarbons, C9, aromatics < 0,1 % cumene) is toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

White Spirit < 2 % aromatics (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics)
Aquatic - Acute toxicity: 96 hours fish (Oncorhynchus mykiss), LL50 > 1000 mg/l
Aquatic - Acute toxicity: 48 hours daphnia magna, EL50 1000 mg/l
Aquatic - Acute toxicity: EL50 > 1000 mg/l (Pseudokirchneriella subcapitata, microalgae)

High aromatic (Hydrocarbons, C9, aromatics < 0,1 % cumene)
Aquatic – Acute toxicity: 48 hours daphnia magna, EL50 3.2 mg/l
Aquatic – Acute toxicity: 96 hours fish (Oncorhynchus mykiss), LL50 9.2 mg/l
Aquatic - Acute toxicity: 72 hours (Pseudokirchneriella subcapitata, microalgae), EL50 2,6-2,9 mg/l

The aluminium paste is classified as harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability:

White spirit (< 2 % aromatics) and high aromatic are expected to be readily biodegradable and degrade rapidly in air.

12.3 Bioaccumulative potential:

No information.

12.4 Mobility in soil:

Aluminium paste is a solid material and is not expected to penetrate into the soil.

12.5 Results of PBT and vPvB assessments:

This product is not, or does not contain, a substance that is a PBT or a vPvB.

12.6 Endocrine disrupting properties:

The product is non-endocrine disrupting.

12.7 Other adverse effects.

No additional information available.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste material in accordance with local, state or federal regulations. Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
European waste catalogue: 170409 – Metal waste contaminated with dangerous substances.
Empty contaminated packaging thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14. TRANSPORT INFORMATION

	ADR/RID	IATA	IMDG
14.1 UN No	1325	1325	1325
14.3 Transport hazard class(es)	4.1	4.1	4.1
14.4 Packing group	II	II	II
EmS No			F-A, S-G
Tunnel category	E		

14.2 UN proper shipping name:

Flammable solid, organic, n.o.s. (contains hydrocarbons, liquid and aluminium powder)

14.5 Environmental hazards: No

14.6 Special precautions for user:

Handling and storage according to section 7.

14.7 Maritime transport in bulk according to IMO instruments:

NA

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Reference: EC no. 1907/2006, EC no. 1272/2008, (EU) 2020/878, IFA-databases on hazardous substances (GESTIS), CSR for aluminium and Material safety data sheet for white spirit < 2 % aromatics and HA = Hydrocarbons, C9, aromatics < 0,1 % cumene.

15.2 Chemical safety assessment: No

SECTION 16. OTHER INFORMATION

H226 Flammable liquid and vapour.
H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 3 = Flammable liquid, category 3
Flam. Sol. 1 = Flammable solid, category 1
STOT SE 3 = Specific organ toxicity – single exposure, category 3
Asp. Tox. 1 = Aspiration hazard, category 1
Aquatic Chronic 2 = Hazardous to the aquatic environment, category 2
Aquatic Chronic 3 = Hazardous to the aquatic environment, category 3

List of abbreviations
ADR Accord Européen relatief au transport international des marchandises dangereuses par Route.
CAS No. Chemical abstracts service number.
CLP Regulation on Classification, Labelling and packaging of Substances and Mixtures.
CSR Chemical safety report
DNEL Derived NO-Effect Level.
EINECS European Inventory of Existing Commercial Substances.
EWC European Waste Catalogue.
IATA International Air Transport Association
ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization
LC Lethal Concentration
LD Lethal Dose
Marpol International Convention for the Prevention of Pollution from ships.
NOAL No observable adverse effect level.
NOEL/NOEC No observed – effect level/concentration.
PBT Persistent, biaccumulative, toxic.
PNEC Predicted No-Effect Concentration.
REACH Registration, Evaluation, Authorisation, and restriction of Chemicals.
RID Règlement concernant le transport international ferroviaire de marchandises dangereuses.
TWA Time-weighted average.
vPvB Very persistent, very biaccumulative

Revision has been done under section 3. Take the place of 2023-09-18.